## Thermal Systems / Accessories

## **Electrical clogging indicator**







## **Technical Data**

order number	HFZVEG15U00
description	Electrical clogging indicator 1/2"BSPP
Body material	brass
O-ring material	NBR
Switching contact	SPDT
Ambient temperature	-13°F to +185°F
Differential pressure setting	19 +/-20% PSI
Max. pressure	6527 PSI
Mounting torque	37 lbf ft
Protection	IP 65
Voltage 14V DC	5 (4) A
Voltage 30V DC	4 (3) A
Voltage 125V AC	5 (3) A
Voltage 250V AC	3 (2) A
Weight	0,40 lbs



This data sheet and the corresponding scale drawings are to be used as a general guideline and technical overview of our products. Please contact us if more exact information is needed. As we are constantly improving our products, their characteristics, dimensions and weights may also change, although we do our best to incorporate these changes continually, as assumes no liability for any information therein, any errors, omissions, misprints, nor any direct or indirect damages, losses or costs resulting therefrom. Any cooling performances and general technical values indicated in this catalogue are measured at a test bench according to asa testing procedures or calculated, based on such tests. They represent a basis for your product selection. Due to different conditions in testing and application environments the performance may also vary by +15%. All sound values are determined in accordance with ISO 9614-2, DIN EN ISO 11203 accuracy class 3 or Machinery Directive 2006/42/EG and are A-rated. At some of the performance measure data, possible differences to competition data are possible. The reason to that are no existing standardized testing procedures on individual subjects. e.g., for cooling performance measurements. Therefore, we recommend all products to be checked under the system operating conditions. This is also true or vibrations and mechanical stress as well as for pressure pasks and thermal stress and any other relevant factors. General tolerances according to DI ISO 12042, it is to stoperited on the actual scale drawing or data sheet. Any form of liability is excluded for the information included in this datasheet. All details and calculation values are checked to the best of our ability, but these do not ensure any intrinsic product properties: due to the wide-ranging possible applications, it is advised that all technical data herewith included be confirmed through testing carried out by the end-user, as a technology Produktions- und Vertriebs GmbH reserves the right to modify the product without